

Tapiflex Excellence 19dB

Datasheet

Classification	Norm	Tarkett Value
Product type	EN ISO 11638	Polyvinyl chloride floor coverings with foam layer (EN 651)
Commercial classification	ISO 10874	34 Very Heavy
Industrial classification	ISO 10874	42 General
Characteristics	Norm	Tarkett Value
Total thickness	ISO 24346	3.25 mm
Wear layer thickness	ISO 24340	0.80 mm
Total weight	ISO 23997	3250 g/m ²
Surface treatment		TEKTANIUM®
Installation method		Glue-Down
Performance for CE Marking	Norm	Tarkett Value
UKCA - DoC certificate		0120-0074-DOC-202205
Declaration of Performance	EN 14041	0120-074-DoP-2024-01
Reaction to fire	EN ISO 13501-1	Bfl-s1 glued over any A2fl or A1fl substrate (concrete) and/or Cfl-s1 glued over any derivate wood substrate
Electrical Propensity	EN 1815	Antistatic (≤ 2 kV)
Thermal resistance (m ² K/W)	EN ISO 10456	0,04 m ² •K/W
Slip resistance	EN 13893	Class DS (μ ≥ 0.30)
Technical Performance	Norm	Tarkett Value
Residual indentation	EN ISO 24343-1	≤ 0.20 mm Average measured value: 0,10 mm
Dimensional stability	EN ISO 23999	≤ 0.40 % Average measured value : ≤ 0.10 %
Impact sound reduction - ΔLw	EN ISO 717/2	19 dB
Drum sound class	NF 531-074	A
Slip resistance	DIN 51130	R10
Furniture leg effect	EN ISO 16581	No damage
Castor chair effect	EN ISO 4918	No damage
Curly resistance to heat	EN ISO 23999	≤ 8mm
Colour fastness to light	EN ISO 105-B02	≥ 6
Chemical resistance	EN ISO 26987	Not affected
Underfloor heating		Suitable (subfloor temperature maximum 27°C)
Sustainability, Environment & Indoor Air Quality	Norm	Tarkett Value
Recyclable		Yes - offcuts through ReStart® (ISO 14021)
Total recycled content		25 %
Carbon Footprint (Cradle-to-Gate, EPD Modules A1-A3)		6.12 kg CO ₂ e /m ²
TVOC emissions after 28 days	EN 16516	Platinum (≤ 10 μg/m ³)
Formaldehyde emission	EN 717-1	E1
Dimensions and designs		
Roll		Roll 2x23m
Number of designs available		93



TEKTANIUM™



The above information is subject to modification for the benefit of further improvement (24/03/2025). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website <https://www.tarkett.com> Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for the instructions.