

Description


Homogeneous monolayer calendered linoleum on jute backing, 4mm thick.

Linospport Classic is compliant with EN14904 standard when associated with Lumaflex Extreme or Energy sub-constructions and treated with specific surface treatment.



PROPERTIES	STANDARDS	LINOSPORT CLASSIC
CLASSIFICATION		
Type of floor covering	EN 14041	One single layer calendered linoleum on jute backing
TECHNICAL CHARACTERISTICS		
Total thickness	ISO 24346 (EN 428)	4mm
Total weight	ISO 23997 (EN 430)	ca. 4.7kg/m ²
Width	ISO 24341 (EN 426)	2m
Length	ISO 24341 (EN 426)	ca. 28lm
REQUIREMENTS FOR SAFE USE		
Friction	EN 13036-4	80 to 110
Shock absorption	EN 14808	-
Vertical deformation	EN 14809	-
Specular gloss	EN ISO 2813	≤30
TECHNICAL PERFORMANCES		
Vertical ball behaviour	EN 12235	-
Reaction to fire	EN 13501-1	Cfl-s1*
Resistance to wear	EN ISO 5470-1	-
Resistance to indentation	EN ISO 24343-1	-
Resistance to a rolling load	EN 1569	-
In room noise	NFS-074	-
Thermal resistance	EN ISO 14456	-

Colours available



* on raw concrete and over Lumaflex sub-constructions

Installation and maintenance guides available on request

Technical data in force as from the date of publication (02/2022).

The values above correspond to laboratory test (no in situ test), and are subject to modifications for the benefit of further improvement.

For more detailed technical information, please contact Tarkett Sports.

Colors of the products shown in the photos or samples are indicative only. There may be differences in color, gloss and embossing structure between the products sold and photos or samples.