


Spirit Soul Glue Down 55.

technical data.

BERRY  ALLOC



	Contains	m ²	Gross Weight (incl. box & pallet)
1 pack Spirit Soul Glue Down 55 planks	10 planks	3,45 m ²	16,49 kg
1 pallet Spirit Soul Glue Down 55 planks	51 packs	175,95 m ²	866,94 kg
1 pack Spirit Soul Glue Down 55 tiles	10 tiles	4,18 m ²	19,14 kg
1 pallet Spirit Soul Glue Down 55 tiles	46 packs	192,31 m ²	908,53 kg
1 pack Spirit Soul Glue Down 55 herringbone	64 planks	4,46 m ²	19,86 kg
1 pallet Spirit Soul Glue Down 55 herringbone	42 packs	187,29 m ²	859,20 kg


Product specifications	Norm	Spirit Soul Glue Down 55 Planks	Spirit Soul Glue Down 55 Tiles	Spirit Soul Glue Down 55 Herringbone
Dimensions	EN ISO 24342	L 1500 x W 230 mm	L 914,4 x W 457,2 mm	L 609,6 x W 114,3 mm
Wear layer	EN ISO 24340	0,55 mm	0,55 mm	0,55 mm
Embossing		wood embossed in register (EIR)	stone embossed	wood embossed in register (EIR) & stone embossed
Total thickness	EN ISO 24346	2,5 mm	2,5 mm	2,5 mm
Locking system		no	no	no
Bevel type		micro V4	micro V4	micro V4
Usage classification	EN ISO 10582	23/33/42	23/33/42	23/33/42
Residential warranty*		lifetime	lifetime	lifetime
Commercial warranty*		10 years	10 years	10 years

* warranty conditions on www.berryalloc.com

Test results	Norm	Results
Underfloor heating	EN ISO 12524	suitable (detailed instructions on www.berryalloc.com)
Castor chair	EN ISO 4918	pass
Fire resistance	EN 13501-1	Bfl-s1
Chemical resistance	EN ISO 26987	OK
Residual indentation	EN ISO 24343-1	≤ 0,10 mm – pass
Thermal resistance	ISO 8302	0,010 m ² K/W
Scratch resistance	EN 16094	MSR-A1/B1
Slip resistance	DIN 51130	R10
	EN ISO 13893	class DS
Pendulum slip resistance (PTV)	EN 16165	36+
Sound reduction: impact sound	EN ISO 10140-3 EN ISO 717-2	2 dB
Dimensional stability	EN ISO 23999	≤ 0,15 % - pass
Light fastness	EN ISO 105-B02	≥ 6 - pass
Static electrical propensity	EN 1815	antistatic (≤ 2 kV)

vinyl planks & tiles.





Spirit Soul Glue Down 55.

technical data.

Composition



- ① Protective PU coating/lacquer*
- ② Wear layer 0,55 mm
- ③ Decor layer
- ④ Backing layer

**for wood products enhanced with the UltraShield Matt technology™ that gives an ultra matt look, ultra scratch resistance & ultra slip resistance*

