

Glue down (regular planks, herringbone planks & tiles)

Version: 04/2024

Glue down	Contains	m ²	Gross Weight
1 pack regular planks ZENN	20 planks	4,34 m ²	19,58 kg
1 pallet regular planks ZENN (incl. pallet)	45 packs	195,09 m ²	901 kg
1 pack tiles ZENN	10 tiles	4,18 m ²	18,93 kg
1 pallet tiles ZENN (incl. pallet)	46 packs	192,31 m ²	891 kg
1 pack Herringbone planks ZENN	64 planks	4,46 m ²	19,86 kg
1 pallet Herringbone planks ZENN (incl. pallet)	42 packs	187,29 m ²	854 kg

Product specifications	Norm	Glue down planks & tiles		
		Regular plank	Herringbone plank	Tile
Dimensions		L 1219,2 x W 177,8 mm	L 609,6 x W 114,3 mm	L 914,4 x W 457,2 mm
Total thickness	EN ISO 24346	2,5 mm	2,5 mm	2,5 mm
Thickness of the wear layer	EN ISO 24340	0,55 mm	0,55 mm	0,55 mm
Locking system		no	no	no
Usage classification	EN ISO 10874	23/33/42	23/33/42	23/33/42
Commercial warranty		10 years	10 years	10 years
Residential warranty		Lifetime	Lifetime	Lifetime

Test results

Underfloor heating		suitable max. 27° (80°F) / electrical floor heating systems: max 60 W/m ²
Castor chair	EN ISO 4918	pass
Fire resistance	EN 13501-1	Bfl-s1
Chemical resistance	EN ISO 26987	OK
Thermal resistance	ISO 8302	0,010 m ² K/W
Residual indentation	EN ISO 24343-1	≤ 0,1mm
Sound reduction: impact sound	EN ISO 10140-3	2 dB
Slip resistance	DIN 51130	R10
	EN ISO 13893	class DS
Dimensional stability	EN ISO 23999	< 0,15 % - pass
Light fastness	EN ISO 105 B02	≥ 6

vinyl planks & tiles.

