

Version: 04/2024

Rigid click	Contains	m ²	Gross Weight
1 pack planks ZENN	10 planks	2,17 m ²	18,53 kg
1 pallet planks ZENN (incl. pallet)	45 packs	97,55 m ²	854 kg
1 pack tiles ZENN	6 tiles	2,51 m ²	21,68 kg
1 pallet tiles ZENN (incl. pallet)	40 packs	100,33 m ²	887 kg

Product specifications	Norm	Rigid click vinyl planks & tiles	
		Plank	Tile
Dimensions		L 1219,2 x W 177,8 mm	L 914,4 x W 457,2 mm
Integrated underlay		4 + 1 mm	4 + 1 mm
Total thickness	EN ISO 24346	5 mm	5 mm
Thickness of the wear layer	EN ISO 24340	0,30 mm	0,30 mm
Locking system		2G	2G
Usage classification	EN ISO 10874	23/32	23/32
Commercial warranty		5 years	5 years
Residential warranty		20 years	20 years

Test results

Underfloor heating		suitable max. 27° (80°F) / electrical floor heating systems: max 60 W/m ²
Castor chair	EN ISO 4918	pass
Fire resistance	EN 13501-1	Bfl-s1
Chemical resistance	EN ISO 26987	OK
Residual indentation	EN ISO 24343-1	≤ 0,1mm
Thermal resistance	ISO 8302	0,025 m ² K/W
Slip resistance	DIN 51130	R10
	EN ISO 13893	class DS
Sound reduction: impact sound	EN ISO 10140-3	19 dB
Dimensional stability	EN ISO 23999	< 0,15 % - pass
Lock Strength	EN ISO 10582	> 1,5 kN/m - pass
Light fastness	EN ISO 105 B02	≥ 6

vinyl planks & tiles.

