

Specifications

CHARACTERISTIC	STANDARD	UNIT	RESULTS
Type of Flooring	EN ISO 10582		PVC Heterogeneous Sheet
Surface Treatment			PUR
Classification	EN ISO 10874		Class 34/43
Weight	EN ISO 23997	kg/sqm	3.05
Width	EN ISO 24342	mm	2,000
Roll Length		m	20
Overall Thickness	EN ISO 24346	mm	2
Wear Layer Thickness	EN ISO 24340	mm	0.7
Wear Resistance	EN 660-2		T
Residual Indentation	EN ISO 24343-1	mm	≤ 0.1
Dimensional Stability	EN ISO 23999	%	< 0.4
Flexibility	ISO 24344		No Crack
Light Fastness	EN ISO 105-B02	mm	≥ 6
Furniture Leg Resistance	EN ISO 16581		No Crack, No Damage
Castor Chair Resistance	EN ISO 4918		Suitable
Reaction to Fire	EN 13501-1		Blf-s1
Stain Resistance	EN ISO 26987		No Damage
Dynamic Coefficient of Friction	EN 13893		Class DS
Slip Resistance	DIN 51130		R10
Acoustic Insulation	EN ISO 717-2	dB	4
Electrostatic Performance	EN 1815	kV	< 2
Thermal Resistance	EN ISO 12667	m2.K/W	0.014
Warranty In Years			15yrs - Commercial
Formaldehyde Group	EN 14041:2004/AC:2006		E1
CE Marking	EN 14041:2004/AC:2006		DOP No16001 DOP 05
TVOC After 28 Days	ISO 16000 06		<100



Blf-s1



Castor
Chair



Anti-slip
DS



A+



DNV-GL



DNV-GL



DNV-GL



floor
score



PHTHALATE
FREE



HEAVY METAL
FREE



All specifications are subject to change without notice.
 CGI rendering shown for illustration purposes only.
 Printed representation of colours may vary from the actual product.
 Please view the actual product prior to purchase.