


## technical specifications

Product Description	<b>Carbon Neutral</b> Multilevel Loop
Yarn	Universal Fibers <sup>®</sup> Thrive <sup>®</sup> matter <b>carbon negative recycled</b> yarn
Tile Dimensions	50cm x 50cm
Pile Yarn Weight	825g/m <sup>2</sup>
Total Weight	4185g/m <sup>2</sup>
Total Thickness	7.5mm
Construction	1/12th gauge - Multilevel loop pile
Tufts per m2 / Pile Density	226,771/m <sup>2</sup>
Backing Description	<b>BioBase<sup>®</sup> recycled</b> backing (recycled BS EN ISO 14021)
Wear Classification	Class 33 heavy commercial use (BS EN 1307)
Luxury Rating Class	LC1
Flammability	Euroclass Bfl-s1
Thermal Resistance	Tog Rating: 0.61
Castor Chair Rating	Pass - continuous use (BS EN 985)
Hexapod	BS ISO 10361: Method B:2000 3 to 4
Static Loading	BS 4939: 1987 (2017) Recovery >80% (24hrs)
Dynamic Loading	BS ISO 2094: 1999 (2005) Loss <20% (1000 impacts)
Body Voltage Test	BS ISO 6356:2000 <2kV
Colour Fastness To Light	BS EN ISO 105 - B02 Minimum Grade 6
Colour Fastness To Shampoo	BS 1006:UK-TB: 1990 Minimum Grade 4-5
Sound Absorption Coefficient	BS EN 354:2003
Reduction in Impact Noise	BS EN ISO 10140-3:2010 24dB
Reduction in Impact Noise at 1000Hz	BS EN ISO 10140-3:2010 40.0dB
Number Of Tiles Per Box	20 (5m <sup>2</sup> )
VOC	Class A+
Warranty	15 years



## eco<sub>2</sub>matters<sup>®</sup>

We are committed to helping deliver a sustainable future, because we believe that what we do **matters**. To help us deliver on this commitment, we have developed **eco<sub>2</sub>matters<sup>®</sup>**, our sustainability principles, supported by independent 3rd party verification.



**Journey to Net Zero**



**Positive Environmental Impact**



**Social Values & Well Being**

**surface trace<sup>®</sup>** delves into our traditional roots and reflects the tactile craft of weaving. A curated colour palette of 12 brings together unexpected tones, hues and contrasts to create a variety of elevated neutrals. Combined with an opulent chunky texture, **surface trace<sup>®</sup>** helps to create calm, quiet and luxurious spaces.



**carbon neutral**

**surface trace<sup>®</sup>** is **carbon neutral**



**carbon negative recycled yarn**

**surface trace<sup>®</sup>** uses Universal Fibers<sup>®</sup> Thrive<sup>®</sup> matter yarn which is C2C Certified Material Health Certificate™ Silver



**BioBase<sup>®</sup> backing**

**surface trace<sup>®</sup>** uses **BioBase<sup>®</sup> recycled** backing



**take back service**

Burmatex<sup>®</sup> **reco<sub>2</sub>very** take back service provides a no landfill solution for your used tiles



**100% certified renewable**

Burmatex<sup>®</sup> products are made using 100% certified **renewable** electricity



**independently 3rd party verified**

**eco<sub>2</sub>matters<sup>®</sup>** declarations are independently 3rd party verified

### EPD

Burmatex<sup>®</sup> products are supported by 3rd party independently verified, product specific EPD's

### LEED

Burmatex<sup>®</sup> products contribute towards Leed accreditation

### SKA

Burmatex<sup>®</sup> products adhere to SKA standards

### WELL Building Standards

Burmatex<sup>®</sup> products contribute to WELL Building Standards

Contact Us  
T +44 (0) 1924 262 525  
email: sales@burmatex.co.uk

Burmatex Ltd  
Victoria Mills, The Green  
Ossett, West Yorkshire  
WF5 0AN, United Kingdom

This shade card is the property of Burmatex<sup>®</sup>  
Made from **eco laminate** and **100% recyclable card**

Burmatex<sup>®</sup> reserves the right to improve the specification of all products without prior notification. E&OE Burmatex<sup>®</sup> carpets, carpet tiles and carpet planks should be installed and used in full accordance with instructions at [www.burmatex.co.uk](http://www.burmatex.co.uk) and recognised trade standards. Orders are subject to Burmatex<sup>®</sup> terms and conditions of sale. See: [www.burmatex.co.uk](http://www.burmatex.co.uk)

LRV values

Product code	Product colour name	CIE Y
36601	mill	20.63
36602	loom	12.77
36603	weave	9.02
36604	knotted	17.44
36605	pin	16.27
36606	frame	15.50
36607	unfold	20.30
36608	tweed	14.66
36609	entwine	7.40
36610	mesh	16.92
36611	aspect	11.23
36612	echo	8.88