
























Technical specifications

Tessera carpet tiles meet the requirements of EN 1307

tessera® harmony

Description	Tufted multi-pile height loop carpet tile	
 Tile size	EN 994	50 cm x 50 cm
 Total thickness	ISO 1765	6.3 mm
Pile height	ISO 1766	3.4 mm
 Collection size	12	
Packaging per carton tiles	16 (4 m ²)	
 Commercial use	EN ISO 10874	Class 33
Pile composition	100% polyamide 6	
Dye method	100% solution dyed	
Stitch density	ISO 1763	255,052 per m ²
 Pile weight	ISO 8543	720 g/m ²
Total weight	ISO 8543	4260 g/m ²
 Primary backing	Polyester	
Secondary backing	ProBac™ modified bitumen and polyester fleece. Contains over 76% recycled content.	
Alternative available secondary backing	SOFTbac®	
 Acoustical impact noise reduction	ISO 10140-3	25 dB
 Acoustical sound absorption	ISO 354	α _w = 0.15 (H)
 Castor chair continuous use	ISO 4918	r ≥ 2.4
 Colour fastness to light	EN ISO 105-B02	≥ 5
 Dimensional stability	EN 986	≤ 0.2 %
 Indoor air emissions: TVOC after 28 days	EN 16516	≤ 0.1 mg/m ³
 Creating Better Environments		
Renewable Energy	All Tessera carpet tiles are manufactured using 100% renewable energy (electricity & biogas)	
Recycled Content	Harmony carpet tiles contain 60% recycled content by weight	
Indoor Air Quality	Harmony carpet tiles comply to Indoor Air Comfort Standards	
 Back to the Floor	Installation off cuts can be collected via Back to the Floor	
Ska Rating	Harmony meets Ska Rating criteria for M12 soft floor coverings in office, retail and higher education schemes	
 Installation method	Monolithic	
Harmony carpet tiles meet the requirements of EN 14041:2004 and BS EN 14041:2004		
  EN 14041 BS EN 14041		
 Product code	EN 14041	1170104-DoP-210
 Product code	BS EN 14041	1170104-DoP-GB210
 Reaction to fire	EN 13501-1	C _f -s1, G, NCS
 Slip resistance	EN 13893	μ ≥ 0.30
 Body voltage	ISO 6356	< 2.0 kV
 Thermal conductivity	EN 12667	0.06 W/mK

Recommended adhesives: For the latest installation instructions and recommended adhesives please visit www.forbo-flooring.co.uk/installation

All Forbo Flooring Systems' sales organisations worldwide have a certified Quality Management System in accordance with ISO 9001.

All Forbo Flooring Systems' manufacturing operations have a certified Environmental Management System in accordance with ISO 14001.

The Life Cycle Assessment (LCA) of Forbo Flooring Systems' products is documented in individual Environmental Product Declarations (EPD's) which can be found on all of our websites.

Tessera is manufactured in a facility certified to SA8000 and ISO 45001.



Whilst Forbo Flooring UK Limited does its best to ensure that the contents of this specification are correct and accurate at the time of publication, to the fullest extent permitted by law, Forbo Flooring UK Limited makes no, and expressly disclaims all, guarantees of any kind, expressed or implied in respect of the information, content, materials or products displayed in this specification and does not represent that the information is accurate, complete or current.



For more information:

e: info.flooring.uk@forbo.com

t: **0800 0282 162**

w: forbo-flooring.co.uk/harmony



FLOORING SYSTEMS