



**Installation Method**



Ashlar

Herringbone

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see [www.interface.com/disclaimer](http://www.interface.com/disclaimer).

**Product** Vintage Kimono **Color** 106593 Taupe **Collection** Embodied Beauty **Backing** CQuest™Bio

**Product Specifications**

Product Number	141780AK0V
Product Construction	Tufted Sheared
Yarn System	Post-Consumer Content Nylon
Yarn Manufacturer	Universal
Dye Method	100% Solution Dyed
Soil/Stain Protection	Protekt <sup>2</sup> ®
Preservative Protection	No Added Preservatives

	Imperial	Metric
Tufted Yarn Weight	26 oz/yd <sup>2</sup>	882 g/m <sup>2</sup>
Machine Gauge	1/10 in	39.4 ends/10cm
Pile Height	0.16 in	4.1 mm
Pile Thickness	0.098 in	2.5 mm
Stitches	8.7 /in	34.3 ends/10cm
Pile Density	9,551 oz/yd <sup>3</sup>	354,149 g/m <sup>3</sup>
Size	9.845 in x 39.38 in	25cm x 1m

**Performance Specifications**

Flooring Radiant Panel	(ASTM E-648) Passes
Smoke Density	(ASTM E 662) ≤ 450
Flammability	Passes Methenamine Pill Test (DOC-FF1-70)
Lightfastness	(AATCC 16 - E) ≥ 4.0 @ 60 AFU's
Static	(AATCC - 134) < 3.0 KV
Dimensional Stability	AACHEN Din 54318 <.10%
Traffic Classification	Heavy
Fiber Modification Ratio	1.7 to 1.9

**Health + Environmental Specifications**

<b>Carbon Footprint</b>	
Embodied Carbon (Cradle to Gate)	2.9 (based upon 20 oz face weight) Kg CO <sub>2</sub> /M <sup>2</sup>
Full Life Cycle Carbon Emissions	Certified Carbon Neutral Floors™
<b>Total Recycled Content</b>	
Recycled Content (Pre Consumer)	59%
Recycled Content (Post Consumer)	2%
Indoor Air Quality	Green Label Plus #100244 CDPH 01350
Material Composition	PVC-free and also free of Added Formaldehyde, Heavy Metals and Ortho Phthalates, Fluorinated Chemicals (PFAS), and Halogenated Flame Retardants.
Disclosure of Environmental Impacts	<a href="#">Environmental Product Declaration</a>
Disclosure of Product Ingredients	Health Product Declaration
LEED v4	Contributes to multiple IEQ and MR credits
End of Life	Carpet to Carpet Recycling through ReEntry®

**Technical Information**

Installation	<a href="#">Interface Installation Guidelines</a>
Maintenance	<a href="#">Recommended Interface Maintenance Guidelines</a>
Reclamation	Recyclable through ReEntry® - Call 1.888.733.6873 (U.S.) / 1.866.398.3191 (Canada)
Warranty	<a href="#">15 Year Standard Carpet Warranty</a>
Installation Method	Ashlar,Herringbone
Standard Backing	CQuest™GB

Backing Options ( <a href="#">Learn more</a> )	CQuest™Bio, CQuest™GB, CushionBac Renew™, ReadyBac™
Tile Size Options	25cm x 1m
Manufacturing Location	<a href="#">ISO 9001 &amp; 14001 Certified facilities in Troup County, Georgia, United States</a>