



Installation Method



Ashlar

Herringbone

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see www.interface.com/disclaimer.

Product Crossroads **Colour** Cornerstone **Collection** Earthen Forms Collection

Product Specifications

Product Number	A034
Product Construction	High Performance Luxury Vinyl Tile contains 39% Pre-Consumer Recycled Content
Finish	Ceramor+™ UV stabilised Ceramic Bead Coating
Wear Layer Thickness	22 mil
Total Thickness	(EN ISO 24346) 4.5 mm
Total Weight	6,320 g/m ²
Size	25cm x 1m
Tiles per Box	10 - 2.5m ²
Backing	Sound Choice+™ Acoustic Backing

Performance Specifications

Wear Classification	EN ISO 10874 33 Heavy Commercial / 42 General Light Industrial
CE Declaration Of Performance	MOC2024-0087
UKCA Declaration of Performance	MOC2024-0087
Castor Chair Rating	(ISO 4918 / EN425) Pass
Flammability	(EN ISO 9239-1) Euroclass Bfl-s1 (EN 13501-1)
Light Fastness	≥6 (ISO 105-B02)
Dimensional Stability	(ISO 23999) ≤ 0.25 %
Curling	≤ 2 mm (ISO 23999)
Residual Indentation	(EN ISO 24343-1) ≤ 0.2 mm
Determination of Anti-Slip	R10 (EN 16165 - Annex B)
Pendulum Wet & Dry 4S	36+ Low slip potential (EN 16165 - Annex C)
Chemical Resistance	(EN ISO 26987) Very Good
Impact Sound Insulation ΔLw EN ISO 10140-3	Upto 19 dB

Environmental Specifications

Environmental Product Declaration	Download EPD
Disclosure of Product Ingredients	Health Product Declaration
Total Recycled Content	39 %
Indoor Air Quality	French A+ Indoor Air Comfort GOLD® LVT Greenguard Gold M1 Emission Certification - LVT
Embodied Carbon (Cradle to Gate)	6.8 kg CO ₂ eq./m ²
Material Composition	Free of Ortho Phthalates

Technical Information

Installation	See recommended LVT installation guidelines
Maintenance	See recommended LVT maintenance guidelines
Warranty	15 years LVT

Certifications

CE

21

Wolpert European Manufacturing DAC
 Industriestrasse 15
 33099 Bielefeld
 Germany
 The Netherlands

EN 15441:2004
 Approved by UKCA

Residual free covering for roof use
 Declaration: Class EN 15441:2004
 Reaction to fire: Class B1 (see EN 13501-1:2007, Annex A1)
 Fire resistance: Class EI 120 (see EN 13501-2:2007, Annex A1)
 Fire resistance: Class EI 120 (see EN 13501-2:2007, Annex A1)
 Acoustic: Class 1 (see EN 12524:2006, Annex A1)
 www.wolpert.com/ukca

**UK
CA**

21

Wolpert European Manufacturing DAC
 Industriestrasse 15
 33099 Bielefeld
 Germany
 The Netherlands

EN 15441:2004
 Approved by UKCA

Residual free covering for roof use
 Declaration: Class EN 15441:2004
 Reaction to fire: Class B1 (see EN 13501-1:2007, Annex A1)
 Fire resistance: Class EI 120 (see EN 13501-2:2007, Annex A1)
 Fire resistance: Class EI 120 (see EN 13501-2:2007, Annex A1)
 Acoustic: Class 1 (see EN 12524:2006, Annex A1)
 www.wolpert.com/ukca