




Installation Method



Ashlar

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see www.interface.com/disclaimer.

Product Heirloom **Colour** Sweetgrass **Collection** Lasting Impressions Collection

Product Specifications

Product Number	A036
Product Construction	High Performance Luxury Vinyl Tile contains 39% Pre-Consumer Recycled Content
Finish	Ceramor+™ UV stabilised Ceramic Bead Coating
Wear Layer Thickness	(EN ISO 24340) 0.55 mm
Total Thickness	(EN ISO 24346) 4.5 mm
Total Weight	6,320 g/m ²
Size	25cm x 1m
Tiles per Box	10 - 2.5m ²
Backing	Sound Choice+™ Acoustic Backing

Performance Specifications

Wear Classification	EN ISO 10874 33 Heavy Commercial / 42 General Light Industrial
CE Declaration Of Performance	MOC2024-0087
UKCA Declaration of Performance	MOC2024-0087
Castor Chair Rating	(ISO 4918 / EN425) Pass
Flammability	(EN ISO 9239-1: 2010) Euroclass Bfl-s1 (EN 13501-1)
Light Fastness	≥6 (ISO 105-B02)
Light Reflectance Value (LRV-L)	64.38
Light Reflectance Value (LRV-Y)	21.32
Curling	≤ 2 mm (ISO 23999)
Residual Indentation	(EN ISO 24343-1) ≤ 0.2 mm
Determination of Anti-Slip	R10 (EN 16165 - Annex B)
Pendulum Wet & Dry 4S	36+ Low slip potential (EN 16165 - Annex C)
Chemical Resistance	(EN ISO 26987) Very Good
Impact Sound Insulation ΔLw EN ISO 10140-3	Upto 19 dB

Environmental Specifications

Environmental Product Declaration	Download EPD
Disclosure of Product Ingredients	Health Product Declaration
Total Recycled Content	39 %
Indoor Air Quality	French A+ Indoor Air Comfort GOLD® LVT Greenguard Gold M1 Emission Certification - LVT FloorScore® SCS-FS-04366
Embodied Carbon (Cradle to Gate)	6.8 kg CO ₂ eq./m ²
Fully Recyclable	Can be recycled into carpet tile backing.
Material Composition	Free of Ortho Phthalates

Technical Information

Installation	See recommended LVT installation guidelines
Maintenance	See recommended LVT maintenance guidelines
Warranty	15 years LVT

Certifications

Upto 19 dB

CE

24

Frankfurt-Europen-Maschinenbau AG
 Industriestraße 15
 60528 Frankfurt
 Telefon +49 69 2124-1000
 Fax +49 69 2124-1001
 E-Mail info@femba.com
www.femba.com

**UK
CA**

26

Frankfurt-Europen-Maschinenbau UK
 Industrial Way 15
 Brentford
 Middlesex
 TW8 9JF
 Telephone +44 181 606 1000
 Fax +44 181 606 1001
 E-Mail info@femba.com
www.femba.com