



Installation Method



Ashlar

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see www.interface.com/disclaimer.

Product Shallows **Colour** Spinifex **Collection** Upon Common Ground Collection
Backing CQuest™Bio

Product Specifications

Product Construction	Tapestry Tufted Patterned Structured Loop Pile
Yarn System	100% Recycled Solution Dyed Yarn
Standard Backing	CQuest™Bio
Size	25cm x 1m
Tiles per Box	12 - 3m ²
Optional Backings	CQuest™Bio SONE CQuest™Bio SONE+

More Product Specifications

Pile Yarn Weight	1,153 g/m ² ± 5%
Total Weight	4,715 g/m ² ± 5%
Pile Height	4 mm +15% / - 10%
Total Thickness	9.4 mm ±0.5mm
Gauge - Ends per 10 cm	1/10 - 39.4
Tufts per m ²	149,488 /m ² ±5%

Performance Specifications

Wear Classification	EN 1307 33 Heavy Contract
Castor Chair Rating	≥ 2.4 (EN 985) Continuous Use
Flammability	(EN ISO 9239-1) Euroclass Bfl-s1 (EN 13501-1)
Light Reflectance Value (LRV-L)	39.91
Light Reflectance Value (LRV-Y)	11.20
Dimensional Stability	≤0.2% (ISO 2551/EN 986)
Impact Sound Insulation ΔLw EN ISO 10140-3	25 dB
Rating of Sound Absorption (αw) EN ISO 11654	0.2
Sound Absorption (αs)EN ISO 354 at 125 Hz	0.02
Sound Absorption (αs)EN ISO 354 at 250 Hz	0.03
Sound Absorption (αs)EN ISO 354 at 500 Hz	0.09
Sound Absorption (αs)EN ISO 354 at 1000 Hz	0.27
Sound Absorption (αs)EN ISO 354 at 2000 Hz	0.45
Sound Absorption (αs)EN ISO 354 at 4000 Hz	0.57

Environmental Specifications

Environmental Product Declaration	Download EPD
Total Recycled Content	83.3 %
Pre-Consumer (Total)	71.10 %
Post-Consumer (Total)	12.20 %
Yarn Recycled Content	100.00 %
Pre-Consumer (Yarn)	50.00 %
Post-Consumer (Yarn)	50.00 %
Total Bio Based Content	8 %
Total Recycled & Bio Based Content	91.3 %
Indoor Air Quality	French A+ M1 Emission Certification -CQB
Indoor Air Quality GUI	GUI Standard
HQE (France)	View Potential HQE Contribution

DGNB (Germany)	View Potential DGNB Contribution
Embodied Carbon (Cradle to Gate)	4.55 kg CO ₂ eq./m ²
Full Life Cycle Carbon	Certified Carbon Neutral Floors™
Installation Waste	Ashlar – 3-5 %
TacTiles®	Optimised for glue-free installation with TacTiles® connectors with virtually zero VOCs
Recycling	Can be returned through the Interface ReEntry scheme and be reused as raw material in new carpet tiles.
ReUse	Can be cleaned and reused in a non-critical location to extend its useful life.
Waste to Energy	Can be incinerated in appropriate waste to energy plant.

Technical Information

Installation	View recommended Interface Installation Guidelines online
Maintenance	View recommended Interface Maintenance guidelines online
Warranty	15 years
Manufacturing Location	ISO 9001, 14001 & 45001 Certified Facilities in Europe

Certifications

 2527C	2527C
	2527C
	EN 1307 33 Heavy Contract
	LC2
	(EN ISO 9239-1) Euroclass Bfl-s1 (EN 13501-1)
	≥ 0,30
	Yes
	25 dB
	0.2
	≥ 7
	≤ 0.2% (ISO 2551/EN 986)
	0.108
	≥ 2.4



Yes

GUI Standard

French A+

2527C