

CRAFTED SERIES

Modern Maker / Woven Colour



| | |
|--------------------------------|--|
| Construction | Tufted, Structured Loop Pile |
| Face Fibre | ECONYL® Type 6 nylon made with 100% regenerated nylon |
| Soil Release | StainSmart® for soil release, liquid repellence |
| Finished Face Weight | 490 g/m ² |
| Gauge | 47.2 / 10 cm |
| Rows | 44 / 10 cm |
| Tuft Density | 224,000 /m ² |
| Finished Pile Height | 2.5 mm |
| Standard Backing | Comfort Lite 90% Recycled content Polyurethane cushion Available with TractionBack® on request |
| Nominal Total Thickness | 8.3 mm |
| Tile Size | 50 cm x 50 cm |
| Nominal Total Weight | 3800 g/m ² |
| Tiles per Box | 22 (5.5m ²) |

PERFORMANCE

| | |
|---|---|
| Flammability (Euroclassification EN13501:1-2002) | Class Bfl - s1 |
| Flammability (Radiant Panel ASTM-E-648) | Class 1 |
| Flammability (Hot Metal Nut BS4790) | Low Radius of Char |
| Use Classification (EN 1307) | Class 33 Heavy Commercial Use |
| Static Electricity (ISO 6356) | Pass ≤ 2.0 KV Permanent Conductive Fibre |
| Impact Sound (ISO 10140-3) | 31 dB |
| Sound Absorption (ISO354) | 0.25 Class E |
| Alpha s values | 125Hz 0.01, 250Hz 0.07, 500Hz 0.59, 1000Hz 0.18, 2000Hz 0.26, 4000Hz 0.36 |

ENVIRONMENTAL

100% regenerated content yarn

90% recycled Polyurethane cushion backing
28.1% recycled content including up to 7% post consumer content

Manufactured in ISO14001 certified location using electricity from renewable sources

GuT & CRI Green Label Plus certified for indoor air quality

EPD verified - BRE certified

WARRANTIES

12 year wear warranty


Lifetime Antistatic guarantee

Latent Defects guarantee

CERTIFICATIONS

| | | | | | | | | | |
|--|--|--|--|--|--|--|--|--|--|
| | | | | | | | | | |
| | | | ECONYL® Made with 100% Regenerated Nylon | | | | | | |

INSTALLATION



CE MARKING

