

# FINE DETAIL

Metallic Joinery / Stitchwork



|                                |   |
|--------------------------------|---|
| <b>Construction</b>            | Tufted, Textured Loop Pile  |
| <b>Face Fibre</b>              | ECONYL® Solution Dyed 100% recycled Nylon 6   |
| <b>Soil Release</b>            | StainSmart® for soil release, liquid repellence (applicable only to the colour Silver Twist)                |
| <b>Finished Face Weight</b>    | 545 - 580 g/m <sup>2</sup>  |
| <b>Gauge</b>                   | 47.2 / 10 cm  |
| <b>Rows</b>                    | 44 / 10 cm  |
| <b>Tuft Density</b>            | 207,680 /m <sup>2</sup>   |
| <b>Finished Pile Height</b>    | 3.6 mm  |
| <b>Standard Backing</b>        | Comfort Lite 90% recycled open cell polyurethane cushion backing<br>Available with TractionBack® on request |
| <b>Nominal Total Thickness</b> | 9.3 mm  |
| <b>Plank Size</b>              | 25 cm x 100 cm  |
| <b>Nominal Total Weight</b>    | 4100 g/m <sup>2</sup>   |
| <b>Planks Per Box</b>          | 10 (2.5m <sup>2</sup> )   |

## PERFORMANCE

|   |   |
|---|---|
| <b>Flammability (Euroclassification EN13501:1-2002)</b> | Class Bfl - s1  |
| <b>Flammability (Radiant Panel ASTM-E-648)</b>          | Class 1   |
| <b>Flammability (Hot Metal Nut BS4790)</b>              | Low Radius of Char  |
| <b>Use Classification (EN 1307)</b>                     | Class 33 Heavy Commercial Use   |
| <b>Castor Chair (BS EN 985:2001)</b>                    | Class A - Intensive use (r value ≥ 2.4)                                   |
| <b>Static Electricity (ISO 6356)</b>                    | Pass ≤ 2.0 KV Permanent Conductive Fibre                                  |
| <b>Impact Sound (ISO 10140-3)</b>                       | 33 dB   |
| <b>Sound Absorption (ISO354)</b>                        | 0.30 (H) Class D  |
| <b>Alpha s values</b>                                   | 125Hz 0.00, 250Hz 0.05, 500Hz 0.30, 1000Hz 0.25, 2000Hz 0.30, 4000Hz 0.35 |

## ENVIRONMENTAL

68% recycled content by total product weight  
 Manufactured in ISO14001 certified location using renewable sources  
 GuT & CRI Green Label Plus certified for indoor air quality  
 EPD verified

## WARRANTIES

12 year wear warranty  
 Lifetime Antistatic guarantee  
 Latent Defects guarantee

## CERTIFICATIONS

|  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
|  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |

## INSTALLATION

|               |             |
|---------------|-------------|
|               |             |
| Ashlar Random | Herringbone |

## CE MARKING

|  |  |  |  |  |  |
|--|--|--|--|--|--|
|  |  |  |  |  |  |
| 13<br>DOP-0338-100402<br>EN 14041:2004 |  |  |  |  |  |