

# OBEX™ TILE: LOOP

SPECIFICATION SHEET DATE: 27 MARCH 2020

## MODULAR TILE

### Construction

Tufted, Multi-Level Loop

### Tile Size

50 cm x 50 cm

### Textile Yarn Type

ECONYL® Type 6 and Monofilament

### Dye Method

Solution-Dyed

### Nominal Tufted Face Weight

946 g/m<sup>2</sup>

### Gauge

1/12

### Stitches Per Centimeter

28.70

### Tufts

2,100/100 cm<sup>2</sup>

### Nominal Pile Height

6.48 mm

### Nominal Total Thickness

9.9 mm

### Nominal Total Weight

3,540 g/m<sup>2</sup>

### Backing Type

PVC-Free WellBAC™ Comfort Cushion

### Recycled Content by Total Weight

33.3% Pre-Consumer  
6.6% Post-Consumer

### Flammability (EN13501:1-2010)

Class Cfl-s1

### Fastness to Rubbing (EN ISO 105/X12)

5

### Lightfastness (EN ISO 105/B01)

>6

### Water Fastness (EN ISO 105/E01)

5

### Shampoo Fastness (BS 1006)

5

### Comfort Class (EN 1307:2014)

33/LC3

### Static Electricity (ISO 6356)

≤2.0 KV

### Recommended Maintenance

Daily Vacuuming and Quarterly Hot Water Extraction

### Indoor Air Quality —

CRI Green Label Plus™  
GLP.793, Carpet Category 5Y

### Recommended Installation Method(s)

Monolithic, Quarter-Turn, Ashlar

**12 Tiles per box (3m<sup>2</sup>)**

## WARRANTIES

1-Year Manufacturing Defect Warranty

5-Year Wear Warranty



Gold or Platinum Certified  
NSF/ANSI 149 - 2007™  
Sustainable Carpet Assessment



This cushion-back carpet tile product is covered by one or more patents, published applications and/or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.