

SCULPTURED FORMS

High Relief / In The Round

Construction	Tufted, Textured Loop Pile
Face Fibre	Solution Dyed Nylon (20% recycled content)
Soil Release	StainSmart® for soil release (on light colours LRV >20)
Finished Face Weight	High Relief 595 g/m ² / In The Round 655 g/m ²
Gauge	47.2 / 10 cm
Rows	43.0 / 10 cm
Tuft Density	203,150 /m ²
Finished Pile Height	3.1 mm
Standard Backing	WellBAC™ Comfort Plus 90% recycled open cell polyurethane cushion backing Available with TractionBack® on request
Nominal Total Thickness	10.5 mm
Tile Size	50 cm x 50 cm
Nominal Total Weight	4400 g/m ²
Tiles per Box	18 (4.5m ²)

PERFORMANCE

Flammability (Euroclassification EN13501:1-2018)	Class Bfl - s1
Flammability (Radiant Panel ASTM-E-648)	Class 1
Flammability (Hot Metal Nut BS4790)	Low Radius of Char
Use Classification (EN 1307)	Class 33 Heavy Commercial Use
Castor Chair (BS EN 985:2001)	Class A - Intensive use (r value ≥ 2.4)
Static Electricity (ISO 6356)	Pass ≤ 2.0 KV Permanent Conductive Fibre
Impact Sound (ISO 10140-3)	34 dB Δw
Sound Absorption (ISO354)	0.30 (H) Class D
Alpha p values	125Hz 0.00, 250Hz 0.10, 500Hz 0.40, 1000Hz 0.25, 2000Hz 0.35, 4000Hz 0.45

ENVIRONMENTAL

60% recycled content by total product weight

Manufactured in ISO14001 certified location using renewable sources

M/PACT Carbon Neutral Floors,
7.65 kg CO₂ e/m² Embodied Carbon (EPD calculation A1-A3)
Cradle to Gate footprint 100% off set

WARRANTIES

15 year wear warranty

Lifetime Antistatic guarantee

Latent Defects guarantee

CERTIFICATIONS

www.millikenfloors.com/gb/tech

INSTALLATION



Monolithic

CE / UKCA

DOP-2895-1004-02 BS EN 14041	DOP-0338-1004-02 BS EN 14041					