

PRIMA

KHROMA COLLECTION

CONSTRUCTION STRUCTURE STRUKTUR STRUCTUUR	Needlefelt Aiguilleté Nadelvlies Naaldvlit	FASTNESS TO LIGHT SOLIDITÉ A LA LUMIÈRE LICHTECHTHEIT LICHTECHTHEID	EN ISO 105-B02 ≥ 5-6
PILE MATERIAL COMPOSITION DU VELOURS POLMATERIAL POOLMATERIAAL	100% PP	COLOUR FASTNESS TO WATER SOLIDITÉ À L'EAU WASSERECHTHEIT WATERECHTHEID	EN ISO 105-E01 ≥ 3-4
SECONDARY BACKING DOSSIER RÜCKEN TAPIJTRUG	Betumen back Min. 70% recycled content	FIRE RESISTANCE COMPORTEMENT AU FEU BRENNVERHALTEN BRANDGEDRAG	EN 13501-1 B _{FL-s1} if glued
PILE WEIGHT POIDS DU VELOURS POLEINSATZGEWICHT POOLGEWICHT	± 900 gr/m ²	SIZE DIMENSION ABMESSUNG AFMETING	50 X 50 cm (1) 100 X 100 cm (2)
TOTAL WEIGHT POIDS TOTAL GESAMTGEWICHT TOTAAL GEWICHT	± 2.735 gr/m ²	PACKAGING EMBALLAGE VERPACKUNG VERPAKKING	5 m ² /b (1) 20 b/p (1) 100 m ² /p (2)
PILE THICKNESS EPAISSEUR DU VELOURS POLDICKE POOLDIKTE	± 5,0 mm		
TOTAL THICKNESS EPAISSEUR TOTALE GESAMTDICKE TOTALE DIKTE	± 7,0 mm		
PRODIS / GUT	36B6F74C		
CLASSIFICATION CLASSEMENT KLASSIFIKATION CLASSIFICATIE	EN 1307 22 - LC2		

itc

ITC CO BV
Kanegemstraat 15, B-8700 Tielt
itc-carpets.com

ERAC

A+
PREZONJE DANJE L'INTERIEUR
A+
A B C

GUT
GUT
GUT



EN 14041 CE
22
ITC CO BV Kanegemstraat 15 - BE 8700 Tielt
DOP: 1010#BJOABV Textile Floor Covering EN 13297 Notified body 2401

myitc-carpets.com