

# REX

## KHROMA COLLECTION

<b>CONSTRUCTION</b> STRUCTURE STRUKTUR STRUCTUUR	Needlefelt Aiguilleté Nadelvlies Naaldvilt	<b>FASTNESS TO LIGHT</b> SOLIDITÉ A LA LUMIÈRE LICHTECHTHEIT LICHTECHTHEID	EN ISO 105-B02 ≥ 5-6
<b>PILE MATERIAL</b> COMPOSITION DU VELOURS POLMATERIAL POOLMATERIAAL	100% PP	<b>COLOUR FASTNESS TO WATER</b> SOLIDITÉ À L'EAU WASSERECHTHEIT WATERECHTHEID	EN ISO 105-E01 ≥ 3-4
<b>SECONDARY BACKING</b> DOSSIER RÜCKEN TAPIJTRUG	Bitumen back Min. 70% recycled content	<b>FIRE RESISTANCE</b> COMPORTEMENT AU FEU BRENNVERHALTEN BRANDGEDRAG	EN 13501-1 B <sub>FL-s1</sub> if glued
<b>PILE WEIGHT</b> POIDS DU VELOURS POLEINSATZGEWICHT POOLGEWICHT	± 650 gr/m <sup>2</sup>	<b>SIZE</b> DIMENSION ABMESSUNG AFMETING	50 X 50 cm
<b>TOTAL WEIGHT</b> POIDS TOTAL GESAMTGEWICHT TOTAAL GEWICHT	± 2.850 gr/m <sup>2</sup>	<b>PACKAGING</b> EMBALLAGE VERPACKUNG VERPAKKING	5 m <sup>2</sup> /b 20 b/p
<b>PILE THICKNESS</b> EPAISSEUR DU VELOURS POLDICKE POOLDIKTE	± 4,0 mm		
<b>TOTAL THICKNESS</b> EPAISSEUR TOTALE GESAMTDICKE TOTALE DIKTE	± 6,0 mm		
<b>PRODIS / GUT</b>	3F58AE27		
<b>CLASSIFICATION</b> CLASSEMENT KLASSIFIKATION CLASSIFICATIE	EN 1307 21 - LC2		



ITC CO BV  
Kanegemstraat 15, B-8700 Tielt  
itc-carpets.com



EN 14041 <b>CE</b>
22
ITC CO BV Kanegemstraat 15 - BE 8700 Tielt
DOP: 1022#BJ0ABV Textile Floor Covering EN 13297 Notified body 2401

myitc-carpets.com