


Heathstar


The Elemental Collection




Style (Méthode de fabrication/ Herstellungsverfahren/ Descripción)	Tufted 1/10" Loop Pile
Yarn Construction (Couche d'usure/ Polmaterial/ Composición fibra)	100% ECONYL® Solution Dyed Nylon - manufactured from recycled fishing nets
Yarn Recycled Content (Contenu velours recyclé/ Recycler Garnanteil/ Contenido de hilo reciclado)	100%
Total Recycled Content (Contenu recyclé total/ Gesamtrecyclinganteil/ Contenido total reciclado)	79%
Pile Yarn Weight (Poids du velours/ Poleinsatzgewicht/ Peso fibra)	730g/m ²
Pile Height (Épaisseur du velours/ Polhöhe/ Altura fibra)	4mm
Pile Density (Densité du velours/ Polrohndichte/ Densidad de fibra)	0.128g/cm ³
Tuft Density (Nombre de touffes/ Noppenzahl/ Densidad del bucle)	177,000/m ²
Total Weight (Poids total/ Gesamtgewicht/ Peso total)	4220g/m ²
Total Thickness (Épaisseur totale/ Gesamtdicke/ Espesor total)	7mm
Backing (Dossier standard/ Standardrückenausstattung/ Tipo de base)	100% Envirobase - contains over 75% recycled materials
Additional Acoustic Backing (Dossier acoustique supplémentaire/ Zusätzliche Akustikrückenausstattung/ Respaldo acústico adicional)	Komfort Bac available on request
Tile Size (Dimension / Abmessung / Tamaño)	50cm x 50cm
Tiles Per Box (Emballage / Verpackung / Embalaje)	20 (5m ²)
Wear Classification (Classement d'usage/ Beanspruchungsbereich/ Clasificación al tráfico)	Heavy Contract Class 33
Luxury Class (Classement de confort/ Komfortklasse/ Clase de lujo)	LC2
Anti-Static Behaviour (Antistatique/ Antistatisch/ Comportamiento antiestático)	Suitable for use with computers. Less than 2Kv
Colour Fastness (Light) (Solidité des couleurs à la lumière/ Lichtechtheit/ Resistencia a la luz solar)	>6
Colour Fastness (Shampoo) (Solidité des couleurs au shampooing/ Farbechtheit (Shamponieren/ Resistencia de los colores al champú)	4-5
Colour Fastness (Dry Rubbing) (Solidité des couleurs au frottement à sec/ Reibechtheit (Trocken)/ Solidez al frote (seco))	4-5
Colour Fastness (Wet Rubbing) (Solidité au frottement au mouillé/ Reibechtheit (Nass)/ Solidez al frote (mojado))	4-5
Flammability BS 4790 Hot Metal Test (Tenue au feu/ Brandverhalten/ Inflamabilidad)	≤ 35mm Low Radius of Char
Flammability BS EN 13501 (Tenue au feu/ Brandverhalten/ Inflamabilidad)	Bfl-s1
Castor Chair Rating (Emploi chaise à roulettes/ Stuhlrolleneignung/ Idoneo para el uso con sillas de ruedas)	r ≥ 2.4 Suitable for intensive use with castor chairs
Dimensional Stability (Stabilité dimensionnelle / Maßbeständigkeit / Estabilidad dimensional)	≤ 0.2%
Impact Sound (Réduction du bruit d'impact/ Trittschallverbesserungsmaß/ Aislamiento a los ruidos de impactos)	Minimum 26dB
Warranty (Garantie/ Garantie/ Garantía)	10 years/ ans /Jahre / años
VOC Content (Contenu en COV/ VOC-Gehalt/ Contenido de COV)	E1 (EN 14041:2004) & Indoor Air Comfort Gold Certified



Broadloom



Tessellated



Random Lay

Please note, for technical reasons, as with all textile materials, it is not possible to colour match from different batches. Orders that need to colour match should be placed at the same time. Production may, therefore, show variations to the sample card. Paragon Carpet Tiles reserves the right to change or modify product specifications without giving prior notice.



BREEAM® A Rated



To place your order

+44 (0)1709 763800 | sales@paragon-carpets.co.uk

More information & samples

paragon-carpets.co.uk | samples@paragon-carpets.co.uk

Paragon Carpet Tiles Farfield Park,
Manvers, Wath-upon-Deerne, Rotherham,
United Kingdom S63 5DB

