

SAFETY DATA SHEET

DCTUK Sticky Stuff Aerosol

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	DCTUK Sticky Stuff Aerosol
Container size	500ml
REACH registration notes	All chemicals used in this product have been registered under REACH where required.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Adhesive.
Uses advised against	Flexible PVC due to the risk of plasticiser migration.

1.3. Details of the supplier of the safety data sheet

Supplier	DCTUK 21 Brookfield Business Park Muir Road Liverpool L9 7AR
	Tel: 0151 705 9520 Web: https://www.dctuk.com/ Email: customerservices@dctuk.com

1.4. Emergency telephone number

Emergency telephone	DCTUK 0151 705 9520 (Mon-Fri 08:00 - 17:30)
---------------------	---

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards	Aerosol 1 - H222, H229
Health hazards	STOT SE 3 - H336
Environmental hazards	Aquatic Chronic 3 - H412

2.2. Label elements

Hazard pictograms



Signal word	Danger
Hazard statements	H222 Extremely flammable aerosol. H229 Pressurised container: may burst if heated. H336 May cause drowsiness or dizziness. H412 Harmful to aquatic life with long lasting effects.

DCTUK Sticky Stuff Aerosol

Precautionary statements	<p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P211 Do not spray on an open flame or other ignition source.</p> <p>P251 Do not pierce or burn, even after use.</p> <p>P261 Avoid breathing vapour/ spray.</p> <p>P273 Avoid release to the environment.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.</p>
Supplemental label information	EUH066 Repeated exposure may cause skin dryness or cracking.
Contains	PENTANE, ACETONE
Supplementary precautionary statements	<p>P271 Use only outdoors or in a well-ventilated area.</p> <p>P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.</p> <p>P302+P352 IF ON SKIN: Wash with plenty of water.</p> <p>P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P314 Get medical advice/ attention if you feel unwell.</p> <p>P391 Collect spillage.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>

2.3. Other hazards

This substance is not classified as PBT or vPvB according to current EU criteria. Containers should be thoroughly emptied before disposal because of the risk of an explosion. In use may form flammable/explosive vapour-air mixture. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

DIMETHYL ETHER			60-100%
CAS number: 115-10-6	EC number: 204-065-8	REACH registration number: 01-2119472128-37-XXXX	
Classification Flam. Gas 1A - H220 Press. Gas (Liq.) - H280			

PENTANE			10-30%
CAS number: 109-66-0	EC number: 203-692-4	REACH registration number: 01-2119459286-30-XXXX	
Classification Flam. Liq. 1 - H224 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411			

DCTUK Sticky Stuff Aerosol

ACETONE		1-5%
CAS number: 67-64-1	EC number: 200-662-2	REACH registration number: 01-2119471330-49-XXXX
Classification Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336		

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Move affected person to fresh air at once. Show this Safety Data Sheet to the medical personnel.
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Keep affected person under observation. If breathing stops, provide artificial respiration. Get medical attention immediately.
Ingestion	Rinse mouth thoroughly with water. Get medical attention. Do not induce vomiting.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if any discomfort continues.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention if irritation persists after washing. If adhesive bonding occurs, do not force eyelids apart.
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue.

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure. Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.
Inhalation	Coughing, chest tightness, feeling of chest pressure. Overexposure to organic solvents may depress the central nervous system, causing dizziness and intoxication and, at very high concentrations, unconsciousness and death.
Ingestion	Ingestion may cause severe irritation of the mouth, the oesophagus and the gastrointestinal tract.
Skin contact	Prolonged contact may cause redness, irritation and dry skin. Product has a defatting effect on skin.
Eye contact	May cause eye irritation. Profuse watering of the eyes.

4.3. Indication of any immediate medical attention and special treatment needed

Specific treatments	If adhesive bonding occurs, do not force eyelids apart.
----------------------------	---

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Water spray, dry powder or carbon dioxide. Alcohol-resistant foam.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

DCTUK Sticky Stuff Aerosol

5.2. Special hazards arising from the substance or mixture

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up. Forms explosive mixtures with air. May explode when heated or when exposed to flames or sparks. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back. Bursting aerosol containers may be propelled from a fire at high speed.

Hazardous combustion products Oxides of carbon. Acrid smoke or fumes.

5.3. Advice for firefighters

Protective actions during firefighting Use water to keep fire exposed containers cool and disperse vapours. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. Keep upwind to avoid inhalation of gases, vapours, fumes and smoke.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet. Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Avoid contact with eyes and prolonged skin contact. No smoking, sparks, flames or other sources of ignition near spillage.

For non-emergency personnel For the greatest protection, clothing should include anti-static overalls, boots and gloves.

For emergency responders For the greatest protection, clothing should include anti-static overalls, boots and gloves.

6.2. Environmental precautions

Environmental precautions Contain spillage with sand, earth or other suitable non-combustible material.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Absorb in vermiculite, dry sand or earth and place into containers. Avoid the spillage or runoff entering drains, sewers or watercourses. Collect spillage for reclamation or disposal in sealed containers via a licensed waste contractor. Avoid water contacting spilled material or leaking containers. Approach the spillage from upwind. Take precautionary measures against static discharge. Use only non-sparking tools. Do not allow material to enter confined spaces, due to the risk of explosion.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Keep away from heat, sparks and open flame. Static electricity and formation of sparks must be prevented. Wear protective clothing as described in Section 8 of this safety data sheet. Read and follow manufacturer's recommendations. Do not use in confined spaces without adequate ventilation and/or respirator. Do not eat, drink or smoke when using this product.

DCTUK Sticky Stuff Aerosol

Advice on general occupational hygiene

Do not eat, drink or smoke when using this product. Remove contaminated clothing and protective equipment before entering eating areas. Wash after use and before eating, smoking and using the toilet. Do not smoke in work area. Clean equipment and the work area every day.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Under normal conditions of handling and storage, spillages from aerosol containers are unlikely. Store in tightly-closed, original container in a dry, cool and well-ventilated place. Store at temperatures not exceeding 50°C.

Storage class

Extremely Flammable Aerosol

7.3. Specific end use(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

DIMETHYL ETHER

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1920 mg/m³

PENTANE

Long-term exposure limit (8-hour TWA): WEL 600 ppm 1800 mg/m³

Short-term exposure limit (15-minute): WEL

ACETONE

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m³

Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m³

WEL = Workplace Exposure Limit.

DIMETHYL ETHER (CAS: 115-10-6)

PNEC

- Fresh water; 0,155 mg/l
- Intermittent release, Water; 1,549 mg/l
- Water; 160 mg/l
- marine water; 0,016 mg/l
- Sediment (Freshwater); 0,681 mg/l
- Sediment (Marinewater); 0,069 mg/l
- Soil; 0,045 mg/l

PENTANE (CAS: 109-66-0)

DNEL

Industry - Dermal; Long term systemic effects: 432 mg/kg/day
 Industry - Inhalation; Long term systemic effects: 3 mg/m³
 Consumer - Dermal; Long term systemic effects: 214 mg/kg/day
 Consumer - Inhalation; Long term systemic effects: 643 mg/m³
 Consumer - Oral; Long term systemic effects: 214 mg/kg/day

ACETONE (CAS: 67-64-1)

DCTUK Sticky Stuff Aerosol

DNEL

Workers - Dermal; Long term : 186 mg/kg/day
 Workers - Inhalation; Short term : 2420 mg/m³
 Workers - Inhalation; Long term : 1210 mg/m³
 Consumer - Oral; Long term : 62 mg/kg/day
 Consumer - Dermal; Long term : 62 mg/kg/day
 Consumer - Inhalation; Long term : 200 mg/m³

PNEC

Fresh water; 10.6 mg/l
 marine water; 1.06 mg/l
 Intermittent release; 21 mg/l
 Sediment (Freshwater); 30.4 mg/kg/day
 Sediment (Marinewater); 3.04 mg/kg/day
 Soil; 33.3 mg/kg/day
 STP; 100 mg/l

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Ensure that the direction of airflow is clearly away from the worker. Use approved respirator if air contamination is above an acceptable level. Observe any occupational exposure limits for the product or ingredients. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof electrical, ventilating and lighting equipment. Ensure operatives are trained to minimise exposure.

Personal protection

Wear protective clothing.

Eye/face protection

Wear chemical splash goggles. Personal protective equipment for eye and face protection should comply with European Standard EN166.

Hand protection

(PE/PA/PE), 2.5mil (0.06mm), >480 min. To protect hands from chemicals, gloves should comply with European Standard EN374. Nitrile rubber. It should be noted that liquid may penetrate the gloves. Frequent changes are recommended.

Other skin and body protection

Provide eyewash station. Avoid contact with skin. Wear suitable coveralls to prevent exposure to the skin.

Hygiene measures

Promptly remove any clothing that becomes contaminated. Wash promptly if skin becomes contaminated. When using do not eat, drink or smoke. Use appropriate hand lotion to prevent defatting and cracking of skin. Wash at the end of each work shift and before eating, smoking and using the toilet.

Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn. In confined or poorly-ventilated spaces, a supplied-air respirator must be worn. Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Wear a respirator fitted with the following cartridge: Gas filter, type AX.

Thermal hazards

Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin.

Environmental exposure controls

Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.

SECTION 9: Physical and chemical properties

DCTUK Sticky Stuff Aerosol

9.1. Information on basic physical and chemical properties

Appearance	Aerosol.
Colour	Amber.
Odour	Aromatic hydrocarbons.
Odour threshold	Data lacking.
pH	pH (concentrated solution): 7-8
Melting point	Data lacking.
Initial boiling point and range	Dimethyl ether: -25°C Pentane: 35°C Acetone: 56°C
Flash point	A flash point method is not available for aerosols, but the major hazardous component, the propellant (dimethyl ether) has a flash point of <-41°C with flammability limits of 3.3% vol. upper and 26.2% vol. lower.
Evaporation rate	Not available.
Evaporation factor	Not available.
Flammability (solid, gas)	No specific test data are available.
Upper/lower flammability or explosive limits	Not available.
Other flammability	No specific test data are available.
Vapour pressure	3 - 6 bar @ 20°C
Vapour density	Not available.
Relative density	Liquid base: 0.75 @ 20°C
Bulk density	Not applicable.
Solubility(ies)	Insoluble in water.
Partition coefficient	Not available.
Auto-ignition temperature	No information available.
Decomposition Temperature	Not available.
Viscosity	Liquid base: 200 - 750 cP @ 20°C 270 - 1000 mm ² /s @ 20°C
Explosive properties	In use may form flammable/explosive vapour-air mixture.
Explosive under the influence of a flame	Yes
Oxidising properties	Does not meet the criteria for classification as oxidising.
9.2. Other information	
Particle size	Not applicable.
Volatile organic compound	This product contains a maximum VOC content of 86 %.

SECTION 10: Stability and reactivity

10.1. Reactivity

DCTUK Sticky Stuff Aerosol

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended. Highly volatile.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Will not polymerise. In use may form flammable/explosive vapour-air mixture. The following materials may react violently with the product: Oxidising materials.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Containers can burst violently or explode when heated, due to excessive pressure build-up. Avoid the accumulation of vapours in low or confined areas.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products Oxides of carbon.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

Summary Based on available data the classification criteria are not met.

Acute toxicity - dermal

Summary Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Summary Based on available data the classification criteria are not met.

Skin corrosion/irritation

Summary Repeated exposure may cause skin dryness or cracking.

Serious eye damage/irritation

Summary Based on available data the classification criteria are not met.

Respiratory sensitisation

Summary Based on available data the classification criteria are not met.

Skin sensitisation

Summary Based on available data the classification criteria are not met.

Germ cell mutagenicity

Summary Based on available data the classification criteria are not met.

Carcinogenicity

Summary Based on available data the classification criteria are not met.

Reproductive toxicity

Summary Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

Summary May cause drowsiness or dizziness.

Target organs Central nervous system

DCTUK Sticky Stuff Aerosol

Specific target organ toxicity - repeated exposure

Summary Based on available data the classification criteria are not met.

Aspiration hazard

Summary Based on available data the classification criteria are not met.

Toxicological information on ingredients.

DIMETHYL ETHER

Acute toxicity - oral

Notes (oral LD₅₀) Not applicable.

Acute toxicity - dermal

Notes (dermal LD₅₀) Not applicable.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) 164000 ppm, Inhalation, Rat

Skin corrosion/irritation

Skin corrosion/irritation Based on available data the classification criteria are not met.

Serious eye damage/irritation

Serious eye damage/irritation Based on available data the classification criteria are not met.

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitro Based on available data the classification criteria are not met.

Genotoxicity - in vivo Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

Reproductive toxicity

Reproductive toxicity - fertility This substance has no evidence of toxicity to reproduction.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Based on available data the classification criteria are not met.

Skin contact

Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin.

Medical symptoms

Symptoms following overexposure may include the following: Arrhythmia (deviation from normal heart beat).

PENTANE

Acute toxicity - oral

DCTUK Sticky Stuff Aerosol

Acute toxicity oral (LD₅₀ mg/kg)	2.0
Species	Rat
<u>Acute toxicity - inhalation</u>	
Acute toxicity inhalation (LC₅₀ vapours mg/l)	25.3
Species	Rat
ATE inhalation (vapours mg/l)	25.3
<u>Respiratory sensitisation</u>	
Respiratory sensitisation	Based on available data the classification criteria are not met.
<u>Skin sensitisation</u>	
Skin sensitisation	Based on available data the classification criteria are not met.
<u>Germ cell mutagenicity</u>	
Genotoxicity - in vitro	Based on available data the classification criteria are not met.
Genotoxicity - in vivo	Based on available data the classification criteria are not met.
<u>Carcinogenicity</u>	
Carcinogenicity	Based on available data the classification criteria are not met.
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	Based on available data the classification criteria are not met.
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	Based on available data the classification criteria are not met.
<u>Aspiration hazard</u>	
Aspiration hazard	May be fatal if swallowed and enters airways.
.	
Skin contact	Repeated exposure may cause skin dryness or cracking.
Eye contact	May cause discomfort.

ACETONE

Toxicological effects	The toxicity of this substance has been assessed during REACH registration.
<u>Acute toxicity - oral</u>	
Acute toxicity oral (LD₅₀ mg/kg)	5,800.0
Species	Rat
ATE oral (mg/kg)	5,800.0
<u>Acute toxicity - dermal</u>	
Acute toxicity dermal (LD₅₀ mg/kg)	15,800.0

DCTUK Sticky Stuff Aerosol

Species	Rat
ATE dermal (mg/kg)	15,800.0
<u>Acute toxicity - inhalation</u>	
Acute toxicity inhalation (LC₅₀ vapours mg/l)	76.0
Species	Rat
ATE inhalation (vapours mg/l)	76.0
<u>Skin sensitisation</u>	
Skin sensitisation	Epidemiological studies have shown no evidence of skin sensitisation.
Skin contact	Irritating to skin.
Eye contact	Irritating to eyes.

SECTION 12: Ecological information

Ecotoxicity Avoid the spillage or runoff entering drains, sewers or watercourses. The product contains substances which are toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

12.1. Toxicity

Toxicity Harmful to aquatic life with long lasting effects.

Ecological information on ingredients.

DIMETHYL ETHER

Acute aquatic toxicity

Acute toxicity - fish	LC ₅₀ , 96 hours: >4000 mg/l, Poecilia reticulata (Guppy)
Acute toxicity - aquatic invertebrates	EC ₅₀ , 48 hours: >4000 mg/l, Daphnia magna LC ₅₀ , 48 hours: 755,549 mg/l, Daphnia magna

PENTANE

Acute aquatic toxicity

Acute toxicity - fish	LC ₅₀ , 96 hours: 4.26 mg/l, Oncorhynchus mykiss (Rainbow trout)
Acute toxicity - aquatic invertebrates	EC ₅₀ , 48 hours: 2.7 mg/l, Daphnia magna
Acute toxicity - aquatic plants	NOEC, 72 hours: 7.51 mg/l, Freshwater algae EC ₅₀ , 72 hours: 10.7 mg/l, Freshwater algae

ACETONE

Acute aquatic toxicity

Acute toxicity - fish	LC ₅₀ , 96 hours: 5540 mg/l, Oncorhynchus mykiss (Rainbow trout)
Acute toxicity - aquatic invertebrates	EC ₅₀ , 48 hours: 8800 mg/l, Daphnia magna

DCTUK Sticky Stuff Aerosol

Acute toxicity - aquatic plants	NOEC, 8 hours: 530 mg/l/8 d, Algae
Acute toxicity - microorganisms	EC ₁₂ , 30 min: 1000 mg/l, Activated sludge
Acute toxicity - terrestrial	LD ₅₀ , 48 hours: 0.1 - 1 mg/cm ² , Eisenia Fetida (Earthworm)
<u>Chronic aquatic toxicity</u>	
Chronic toxicity - aquatic invertebrates	NOEC, 28 days: 2212 mg/l, Daphnia magna

12.2. Persistence and degradability

Persistence and degradability No data available.

Ecological information on ingredients.

DIMETHYL ETHER

Persistence and degradability	Not readily biodegradable.
-------------------------------	----------------------------

PENTANE

Persistence and degradability	The product is biodegradable. Volatile substances are degraded in the atmosphere within a few days.
-------------------------------	---

ACETONE

Persistence and degradability	The product is readily biodegradable.
-------------------------------	---------------------------------------

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not available.

Ecological information on ingredients.

DIMETHYL ETHER

Bioaccumulative potential	No data available on bioaccumulation.
---------------------------	---------------------------------------

PENTANE

Bioaccumulative potential	Not determined.
---------------------------	-----------------

ACETONE

Bioaccumulative potential	BCF: 3, Estimated value.
---------------------------	--------------------------

12.4. Mobility in soil

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

Ecological information on ingredients.

DIMETHYL ETHER

DCTUK Sticky Stuff Aerosol

Mobility Koc: 7,759

PENTANE

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

ACETONE

Mobility Mobile.

Adsorption/desorption coefficient Soil - Kd: 1.5 L/kg @ 20°C

Henry's law constant 2.929 - 2.070 Pa m³/mol @ 25°C water
3.311 Pa m³/mol @ 25°C marine water

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

Ecological information on ingredients.

DIMETHYL ETHER

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

PENTANE

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

ACETONE

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Other adverse effects None known.

Ecological information on ingredients.

PENTANE

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Ensure containers are empty before discarding (explosion risk). Do not puncture or incinerate, even when empty. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Waste class Empty Aerosol: 15 01 10 (Containing hazardous residues), Empty Aerosol: 15 01 04 (No hazardous residues). Full or Partially Empty Aerosol: 16 05 04,

DCTUK Sticky Stuff Aerosol

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID)	1950
UN No. (IMDG)	1950
UN No. (ICAO)	1950
UN No. (ADN)	1950

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	AEROSOLS
Proper shipping name (IMDG)	AEROSOLS
Proper shipping name (ICAO)	AEROSOLS
Proper shipping name (ADN)	AEROSOLS

14.3. Transport hazard class(es)

ADR/RID class	2.1
ADR/RID classification code	5F
ADR/RID label	2.1
IMDG class	2.1
ICAO class/division	2.1
ADN class	2.1

Transport labels



14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant
No.

14.6. Special precautions for user

IMDG Code segregation group	SG69, SW1, SW22
EmS	F-D, S-U
ADR transport category	2
Tunnel restriction code	(D)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

DCTUK Sticky Stuff Aerosol

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	Control of Substances Hazardous to Health Regulations 2002 (as amended). Health and Safety at Work etc. Act 1974 (as amended).
EU legislation	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
Authorisations (Annex XIV Regulation 1907/2006)	No specific authorisations are known for this product.
Restrictions (Annex XVII Regulation 1907/2006)	No specific restrictions on use are known for this product.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

Inventories

EU - EINECS/ELINCS

All the ingredients are listed or exempt.

Canada - DSL/NDSL

All the ingredients are listed or exempt.

US - TSCA

All the ingredients are listed or exempt.

US - TSCA 12(b) Export Notification

None of the ingredients are listed or exempt.

Australia - AICS

All the ingredients are listed or exempt.

Japan - ENCS

All the ingredients are listed or exempt.

Korea - KECI

All the ingredients are listed or exempt.

China - IECSC

All the ingredients are listed or exempt.

Philippines – PICCS

All the ingredients are listed or exempt.

New Zealand - NZIOC

All the ingredients are listed or exempt.

Taiwan - TCSI

All the ingredients are listed or exempt.

SECTION 16: Other information

DCTUK Sticky Stuff Aerosol

Classification procedures according to Regulation (EC) 1272/2008	Aerosol 1 - H222, H229: Weight of evidence. STOT SE 3 - H336, Aquatic Chronic 3 - H412: Calculation method.
Issued by	Technical Department
Revision date	14/01/2021
Revision	1.1
Supersedes date	01/02/2018
SDS number	22023
Hazard statements in full	H220 Extremely flammable gas. H222 Extremely flammable aerosol. H224 Extremely flammable liquid and vapour. H225 Highly flammable liquid and vapour. H229 Pressurised container: may burst if heated. H280 Contains gas under pressure; may explode if heated. H304 May be fatal if swallowed and enters airways. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.