

TILT (Tarkett Interlocking Tiles)

Datasheet

Classification	Norm	Tarkett Value
Product type	EN ISO 10582	Heterogeneous poly(vinyl chloride) floor coverings (ISO 10582)
Domestic classification	EN ISO 10874	23 Heavy
Commercial classification	EN ISO 10874	34 Very Heavy
Industrial classification	EN ISO 10874	43 Heavy
Characteristics	Norm	Tarkett Value
Total thickness	EN ISO 24346	5 mm
Wear layer thickness	EN ISO 24340	0.70 mm
Total weight	EN ISO 23997	8000 g/m ²
Binder content	EN ISO 10582	Type I
Surface treatment		TopClean XP
Bevelled edges		No
Installation method		Interlocking
Performance for CE Marking	Norm	Tarkett Value
Declaration of Performance	EN 14041	0131-0054-DoP-2015-01
Technical Performance	Norm	Tarkett Value
Dimensional stability	EN ISO 23999	Average measured value : ≤ 0.15 %
Curl resistance to heat	EN ISO 23999	≤ 1mm
Reaction to fire	EN 13501-1	Bfl-s1
Residual indentation	EN ISO 24343-1	≤ 0.10 mm
Furniture leg effect	EN ISO 16581	No damage
Castor chair effect	EN ISO 4918	No damage
Impact sound reduction - ΔLw	EN ISO 717-2	6 dB
Thermal resistance (m ² K/W)	EN ISO 10456	0,05 m ² •K/W
Colour fastness to light	EN ISO 105-B02	≥ 6
Chemical resistance	EN ISO 26987	Good resistance
Slip resistance	DIN 51130	R9
Slip resistance	EN 13893	Class DS (μ ≥ 0.30)
Peeling Resistance	EN ISO 24345	≥ 50N/50mm
Electrical Propensity	EN 1815	Antistatic (≤ 2 kV)
Underfloor heating		Suitable (subfloor temperature maximum 27°C)
Sustainability, Environment & Indoor Air Quality	Norm	Tarkett Value
Recyclability through ReStart®		Recyclable
ReStart® Ready		Yes
Phthalate free		Yes
TVOC emissions after 28 days	EN 16516	Gold
Formaldehyde emission class		E1
French emissions label		A+
Dimensions and designs		
Tile	Tile 457.2x457.2mm (18x18") - 10 Tiles=2.09 m ² /box - 48 boxes/pallet Tile 914.4x914.4mm (36x36") - 3 Tiles=2.51 m ² /box - 37 boxes/pallet	
Number of designs available	8	



The above information is subject to modification for the benefit of further improvement (05/09/2023). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website <https://www.tarkett.com> Tarkett's instructions regarding installation, cleaning and maintenance should be observed.

Please contact Tarkett at the address shown for the instructions.